. brilumen

DESCRIPTION

NOTE: The price listed below is for 1 meter. The item is sold in 5 meters reel, so the minimum order is 5 meters. Please insert 5 units into the shopping cart, or multiples of this value.

During the day, at work or at home, the activities we carry out may vary, requiring constant regulation of our attention span. There are several ways to make this adaptation easier and one of them is the room colour temperature regulation while you are performing the different tasks. With the Tunable White LED Strip and the right controller, you can control this factor. If you are looking for a relaxed environment that promotes creativity or relaxation, you can set the temperature to warm colours, up to 3000K. However, if you want to start a task that requires full concentration or the physical activity increase, the temperature of this LED strip can be set to cool colours, up to 6500K. In addition, using the DALI protocol, the Tunable White LED strip can be configured to automatically change the light intensity and colour temperature throughout the day, to properly adapt the human body to the light variations, and to provide hours of rest with a higher quality. This special LED Strip with 14.4W/m and 560 lumens/ meter is an important tool for work or domestic activity, it is very reliable, flexible and easy to install. You can also put LED strip inside an aluminium profile, to further extend its operating cycle.

POWER SUPPLY

12V / 50-60 Hz

LED FEATURES

ICONOGRAPHY



TECHNICAL DRAWING



2002-1112 TW 14,4W 60LED

PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - TUNABLE WHITE SMD5050 14,4W 60 LED IP20

TROBUCT TABLE AND TECHNICAE STECHTICATIONS - TONABLE WITTE SMD5050 14,4W 00 EED II 20							
						CODE	
8	12V		560	70	5MT	2002-1112	

1

ACCESSORI	FS
ACCESSORI	

11	Trix aluminium profile	
	Trix aluminium profile	8010-2002.AL
	IP20 LED Strip Connector	
	IP20 LED Strip Connector	8013-0014
	0	
\rightarrow	Connector w/ binder 15cm Connector w/ binder 15cm	8013-0015
\mathcal{O}^{ϵ}		
	Double c/t w/ binder	
<u>a</u>	Double c/t w/ binder	8013-0016
	L connector	
	L connector	8013-0017
	12,5 mm Connector 12,5 mm Connector	8013-0026
		0013-0020

. brilumen

	OP23 Corner Profile OP23 Corner Profile	SEM TITULO - G810-4052
	LP05 aluminium profile LP05 aluminium profile	SEM TITULO - G810-5201
	LP03 Recessed Profile LP03 Recessed Profile	SEM TITULO - G810-6032
	LP08 Recessed Profile LP08 Recessed Profile	SEM TITULO - G810-6082
J).	LP10 aluminium profile LP10 aluminium profile	SEM TITULO - G810-7012
	NP04 aluminium profile NP04 aluminium profile	SEM TITULO - G820-1012
	NP06 aluminium profile NP06 aluminium profile	SEM TITULO - G830-1017
	NP07 Recessed Profile NP07 Recessed Profile	SEM TITULO - G830-5015
	NP17 aluminium profile NP17 aluminium profile	SEM TITULO - G810-2026
AND	FP02 Edging Tile Profile FP02 Edging Tile Profile	SEM TITULO - G810-2034
	OP15 aluminium profile OP15 aluminium profile	SEM TITULO - G810-2062
	LP06 aluminium profile LP06 aluminium profile	SEM TITULO - G810-6062