

DESCRIPTION

Brilumen features a collection of versatile, modern and stylish wall light fittings and which, depending on the design, beam angle and lumens, are suitable for different types of outdoor areas. If the goal is to light both up and down, Marley, Miller and Tosh are the best option, not forgetting that this last wall light has an optional reflector that allows you to close the beam angle. If you want to get a linear light line, the Wailer 16W is the right light fitting. However, if you are looking for a wall lighting to light a pathway, the recessed Levy 4W completes the goal efficiently. These products have an IP54 and are available in dark grey finish.


| | |
|--------------------|---------------------|
| MOUNTING TYPE | Surface |
| LIGHT DISTRIBUTION | Direct |
| POWER SUPPLY | 220-230V / 50-60 Hz |
| WARRANTY | 2 Years |
| FINISHING | TG |
| CONTROL | ON/OFF |




LED FEATURES

| | |
|----------------------|-----------------|
| LUMINOUS EFFICIENCY | UP TO 65 lm/W |
| CRI | CRI→80 |
| LIFESPAN | 30000h Tp55 |
| STEPS MACADAM | 3 Steps MacAdam |
| LUMEN MAINTENANCE | L90/B50 |
| PHOTOBIOLOGICAL RISK | RG1 |

TECHNICAL DRAWING



ICONOGRAPHY



WAILER 16W
PRODUCT TABLE AND TECHNICAL SPECIFICATIONS - CRI→80

| LENGTH | POWER | FINISHING | CONTROL TYPE | BEAM ANGLE | LED LUMENS | LUMINAIRE LM | COLOR TEMP. | CODE |
|--------|-------|-----------|--------------|------------|------------|--------------|-------------|--------------|
| 500 | 16 | TG | NF | 105 | 998 | 707 | 3000K | 508.80.BA.30 |
| 500 | 16 | TG | NF | 105 | 1049 | 743 | 4000K | 508.80.BA.40 |

SELECT YOUR PREFERRED
OPTION

CONTROL TYPE
XX
ON/OFF NF