

DESCRIÇÃO

FOLLOW-ME EVO is an emergency exit luminaire with a double-sided pictogram. Allows installation as SURFACE, RECESSED, SUSPENDED, or WALL MOUNTED. The body is made of aluminum with a white thermolacquered finish, and the backlit panel is made of clear acrylic, where the exit signaling pictogram is applied.

This luminaire features an integrated battery that provides 3h of autonomy in case of power failure and is visible up to 24 meters away.

The base version includes a "Rest Mode" function for inhibition with remote control signal between 5V and 20V, which safeguards the battery when common lighting is turned off and emergency lighting is not needed. The DALI version can be integrated into an advanced emergency lighting management system, under the DALI protocol.

It includes a self-test function and an LED indicator of the luminaire's status. Additionally, it has a manual test button on the side of the light.

The product complies with the latest standards regarding dimensions and pictogram formats (ISO $\,$ 3864 and EN 60598-2-22), ensuring that it meets the safety and quality standards required.

FOLLOW ME EVO offers the possibility, whitin the same luminaire, to define a "maintained" or "nonmaintained" operating mode at the installation site. By default, it is configured as "non-maintained," but simply connecting a phase line to "SL" (Switched Line) terminal makes it "maintained". This provides convenience and savings, eliminating the need to order different luminaires for each operating mode.



Rated luminous flux - 110 lm

Input voltage - 220-240 VAC

Frequency - 50/60 Hz

Remote control voltage range - 5-20 VDC

Battery type - Li-ion 3.6V 2500mAh

Discharging time - 3h

Charging time - 8h

Operating temperature - 0°C ~ 40°C

Battery lifetime - 1500 cycles

Dimensions - 284x215x35 mm

Materials:

- Fixture aluminium
- Signalling acrylic
- PCB CEM-1 flame-retardant

OPERATING MODES

MAINTAINED

- Continuously ON.
- Power: 1,5W (in normal or emergency operation)


NON-MAINTAINED

- ON only in case of a power failure.
- Power: 0,5W in standby mode and 1,5W in emergency mode

FUENTE DE ALIMENTACIÓN 220-240 VAC / 50-60 Hz



DISEÑO TÉCNICO





CARACTERÍSTICAS DEL LED

ICONOGRAFÍA





FOLLOW-ME EVO BASIC TABLA DE PRODUCTOS Y ESPECIFICACIONES TÉCNICAS - FOLLOW-ME EVO

POTENCIA	MONTAGEM	CÓDIGO
1.5	Basic	612.XX.0011
1.5	Basic	612.XX.0012
1.5	Basic	612.XX.0013
1.5	Basic	612.XX.0014
1.5	Basic	612.XX.0015
1.5	Basic	612.XX.0016
1.5	Basic	612.XX.0017

SELECCIONA TU OPCIÓN	CONTROL TIPO	XX	PICTOGRAM	PI
PREFERIDA	DALI	DL	→	0011
	Rest Mode	RM	←	0012
			•	0013
			¥	0014
			7	0015
			Ľ	0016
			K	0017