



ORIS+ HP PRISMÁTICO - SALIENTE
LISTA PRODUCTO PRECIO - CRI→80

LONGITUD	POTENCIA	LED LUMENS	ACABADO	TEMP. COLOR	CONTROL	REF	PVP
1130	33	6679	AL, TB, TW	4000K	1-10V	156BA.11P8.840.FI	237.1 ☐
					DALI / PUSH Dim	156BA.11P8.840.FI	259 ☐
					ON/OFF	156BA.11P8.840.FI	180.6 ☐
1130	33	6765	AL, TB, TW	5000K	1-10V	156BA.11P8.850.FI	237.1 ☐
					DALI / PUSH Dim	156BA.11P8.850.FI	259 ☐
					ON/OFF	156BA.11P8.850.FI	180.6 ☐
1690	49.5	10019	AL, TB, TW	4000K	1-10V	156BA.16P8.840.FI	303.5 ☐
					DALI / PUSH Dim	156BA.16P8.840.FI	332.3 ☐
					ON/OFF	156BA.16P8.840.FI	253.9 ☐
1690	49.5	10148	AL, TB, TW	5000K	1-10V	156BA.16P8.850.FI	303.5 ☐
					DALI / PUSH Dim	156BA.16P8.850.FI	332.3 ☐
					ON/OFF	156BA.16P8.850.FI	253.9 ☐
2250	66	13358	AL, TB, TW	4000K	1-10V	156BA.22P8.840.FI	466 ☐
					DALI / PUSH Dim	156BA.22P8.840.FI	525.5 ☐
					ON/OFF	156BA.22P8.840.FI	364 ☐
2250	66	13530	AL, TB, TW	5000K	1-10V	156BA.22P8.850.FI	466 ☐
					DALI / PUSH Dim	156BA.22P8.850.FI	525.5 ☐
					ON/OFF	156BA.22P8.850.FI	364 ☐
2810	82.5	16698	AL, TB, TW	4000K	1-10V	156BA.28P8.840.FI	537.2 ☐
					DALI / PUSH Dim	156BA.28P8.840.FI	596.8 ☐
					ON/OFF	156BA.28P8.840.FI	435.3 ☐
2810	82.5	16913	AL, TB, TW	5000K	1-10V	156BA.28P8.850.FI	537.2 ☐
					DALI / PUSH Dim	156BA.28P8.850.FI	596.8 ☐
					ON/OFF	156BA.28P8.850.FI	435.3 ☐
3370	99	20038	AL, TB, TW	4000K	1-10V	156BA.33P8.840.FI	627.9 ☐
					DALI / PUSH Dim	156BA.33P8.840.FI	687.4 ☐
					ON/OFF	156BA.33P8.840.FI	525.9 ☐
3370	99	20296	AL, TB, TW	5000K	1-10V	156BA.33P8.850.FI	627.9 ☐
					DALI / PUSH Dim	156BA.33P8.850.FI	687.4 ☐
					ON/OFF	156BA.33P8.850.FI	525.9 ☐

SELECCIONA TU OPCIÓN
PREFERIDA

ACABADO	FI	ÁNGULO	BA
Anodizado aluminio	AL	80°	80
Negro texturizado	TB		
Blanco texturizado	TW		