


ORIS+ EFFICIENCY L. GLARE - SALIENTE
LISTA PRODUTO PREÇO - CRI→90

COMPRIMENTO	POTÊNCIA	LED LUMENS	ACABAMENTO	TEMP. COR	CONTROLO	REF	PVP
850	39.4	2850	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.08U4.930.FI 214BA.08U4.930.FI	226.2 ☐ 198.4 ☐
850	39.4	3075	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.08U4.940.FI 214BA.08U4.940.FI	226.2 ☐ 198.4 ☐
1130	52.5	3800	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.11U4.930.FI 214BA.11U4.930.FI	260.6 ☐ 233 ☐
1130	52.5	4100	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.11U4.940.FI 214BA.11U4.940.FI	260.6 ☐ 233 ☐
1410	65.7	4750	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.14U4.930.FI 214BA.14U4.930.FI	304.9 ☐ 277.3 ☐
1410	65.7	5125	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.14U4.940.FI 214BA.14U4.940.FI	304.9 ☐ 277.3 ☐
1690	78.8	5700	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.16U4.930.FI 214BA.16U4.930.FI	389.5 ☐ 336.4 ☐
1690	78.8	6150	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.16U4.940.FI 214BA.16U4.940.FI	389.5 ☐ 336.4 ☐
1970	91.9	6650	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.19U4.930.FI 214BA.19U4.930.FI	462.5 ☐ 409.3 ☐
1970	91.9	7175	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.19U4.940.FI 214BA.19U4.940.FI	462.5 ☐ 409.3 ☐
2250	105	7600	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.22U4.930.FI 214BA.22U4.930.FI	510.7 ☐ 457.5 ☐
2250	105	8200	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.22U4.940.FI 214BA.22U4.940.FI	510.7 ☐ 457.5 ☐
2530	118.2	8550	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.25U4.930.FI 214BA.25U4.930.FI	553.1 ☐ 500 ☐
2530	118.2	9225	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.25U4.940.FI 214BA.25U4.940.FI	553.1 ☐ 500 ☐
2810	131.3	9500	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.28U4.930.FI 214BA.28U4.930.FI	601.3 ☐ 548.2 ☐
2810	131.3	10250	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.28U4.940.FI 214BA.28U4.940.FI	601.3 ☐ 548.2 ☐
3090	144.4	10450	TB	3000K	DALI / PUSH Dim ON/OFF	214BA.30U4.930.FI 214BA.30U4.930.FI	658.4 ☐ 605.2 ☐
3090	144.4	11275	TB	4000K	DALI / PUSH Dim ON/OFF	214BA.30U4.940.FI 214BA.30U4.940.FI	658.4 ☐ 605.2 ☐

SELECIONE A OPÇÃO PREFERIDA

ACABAMENTO	FI	ÂNGULO	BA
Preto Texturado	TB	45°	45