


 ORIS SL. PRO C. D/I PR+L3 - TETO
 LISTA PRODUTO PREÇO - CRI→90

COMPRIMENTO	POTÊNCIA	LED LUMENS	ACABAMENTO	TEMP. COR	CONTROLO	REF	PVP
1700	32.9	5067	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	486BA.17P8.930.FI 486BA.17P8.930.FI	708.6 ☐ 585 ☐
1700	32.9	5067	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	486BA.17P8.940.FI 486BA.17P8.940.FI	708.6 ☐ 585 ☐
1980	39.6	6127	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	486BA.19P8.930.FI 486BA.19P8.930.FI	772.5 ☐ 646.8 ☐
1980	39.6	6127	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	486BA.19P8.940.FI 486BA.19P8.940.FI	772.5 ☐ 646.8 ☐
2260	46.3	7188	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	486BA.22P8.930.FI 486BA.22P8.930.FI	943.5 ☐ 749.6 ☐
2260	46.3	7188	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	486BA.22P8.940.FI 486BA.22P8.940.FI	943.5 ☐ 749.6 ☐
2540	53	8249	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	486BA.25P8.930.FI 486BA.25P8.930.FI	999.2 ☐ 814.6 ☐
2540	53	8249	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	486BA.25P8.940.FI 486BA.25P8.940.FI	999.2 ☐ 814.6 ☐
2825	59.7	9310	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	486BA.28P8.930.FI 486BA.28P8.930.FI	1054.9 ☐ 879.6 ☐
2825	59.7	9310	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	486BA.28P8.940.FI 486BA.28P8.940.FI	1054.9 ☐ 879.6 ☐

SELECIONE A OPÇÃO PREFERIDA

ACABAMENTO	FI	ÂNGULO	BA
Preto Texturado	TB	90°	90
Prateado Texturado	TS		
Branco Texturado	TW		

ACESSÓRIOS



C. de Alim. Encastrada	Preto Texturado	PVP	Prateado Texturado	PVP	Branco Texturado	PVP
C. de Alim. Encastrada	80303020.TB	12.00	80303020.TS	12.00	80303020.TW	12.00



C. de Alim. Saliente	Preto Texturado	PVP	Prateado Texturado	PVP	Branco Texturado	PVP
C. de Alim. Saliente	80303021.TB	16.40	80303021.TS	16.40	80303021.TW	16.40



Cabo Aliment. Transpar.	ON/OFF	PVP	DALI Push	PVP
Cabo de Aliment. 1.5m	80303001	5.80	80303004	12.90
Cabo de Aliment. 3m	80303002	11.00	80303005	24.40
Cabo de Aliment. 5m	80303003	20.10	80303006	40.00



Kit de suspensão	Prateado	PVP
Kit Suspensão 1,5 m (1un)	80303017.SL	7.00
Kit Suspensão 3 m (1un)	80303018.SL	16.90
Kit Suspensão 5 m (1un)	80303019.SL	25.60