

ORIS SLIM PRO PRISMÁTICO - TETO
LISTA PRODUTO PREÇO - CRI→90

COMPRIMENTO	POTÊNCIA	LED LUMENS	ACABAMENTO	TEMP. COR	CONTROLO	REF	PVP
570	10.7	2102	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.05P8.930.FI 5241BA.05P8.930.FI	210.7 ☐ 166 ☐
570	10.7	2156	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.05P8.940.FI 5241BA.05P8.940.FI	210.7 ☐ 166 ☐
850	16.1	3153	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.08P8.930.FI 5241BA.08P8.930.FI	266.3 ☐ 224.1 ☐
850	16.1	3234	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.08P8.940.FI 5241BA.08P8.940.FI	266.3 ☐ 224.1 ☐
1130	21.5	4204	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.11P8.930.FI 5241BA.11P8.930.FI	303.3 ☐ 263.1 ☐
1130	21.5	4311	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.11P8.940.FI 5241BA.11P8.940.FI	303.3 ☐ 263.1 ☐
1410	26.8	5255	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.14P8.930.FI 5241BA.14P8.930.FI	354.6 ☐ 316.5 ☐
1410	26.8	5389	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.14P8.940.FI 5241BA.14P8.940.FI	354.6 ☐ 316.5 ☐
1690	32.2	6306	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.16P8.930.FI 5241BA.16P8.930.FI	476.8 ☐ 390 ☐
1690	32.2	6467	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.16P8.940.FI 5241BA.16P8.940.FI	476.8 ☐ 390 ☐
1970	37.5	7357	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.19P8.930.FI 5241BA.19P8.930.FI	522.7 ☐ 438.1 ☐
1970	37.5	7545	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.19P8.940.FI 5241BA.19P8.940.FI	522.7 ☐ 438.1 ☐
2250	42.9	8408	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.22P8.930.FI 5241BA.22P8.930.FI	570 ☐ 487.4 ☐
2250	42.9	8623	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.22P8.940.FI 5241BA.22P8.940.FI	570 ☐ 487.4 ☐
2530	48.3	9459	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.25P8.930.FI 5241BA.25P8.930.FI	619.2 ☐ 539.2 ☐
2530	48.3	9701	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.25P8.940.FI 5241BA.25P8.940.FI	619.2 ☐ 539.2 ☐
2810	53.6	10511	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.28P8.930.FI 5241BA.28P8.930.FI	670.4 ☐ 592.4 ☐
2810	53.6	10779	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.28P8.940.FI 5241BA.28P8.940.FI	670.4 ☐ 592.4 ☐
3090	59	11562	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.30P8.930.FI 5241BA.30P8.930.FI	722.3 ☐ 646.6 ☐
3090	59	11856	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.30P8.940.FI 5241BA.30P8.940.FI	722.3 ☐ 646.6 ☐
3370	64.4	12613	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5241BA.33P8.930.FI 5241BA.33P8.930.FI	771.5 ☐ 698.2 ☐
3370	64.4	12934	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5241BA.33P8.940.FI 5241BA.33P8.940.FI	771.5 ☐ 698.2 ☐

SELECIONE A Opção PREFERIDA

ACABAMENTO	FI	ÂNGULO	BA
Preto Texturado	TB	80°	80
Prateado Texturado	TS		
Branco Texturado	TW		