


 ORIS SLIM PRO LOW GLARE - TETO
 LISTA PRODUTO PREÇO - CRI→90

COMPRIMENTO	POTÊNCIA	LED LUMENS	ACABAMENTO	TEMP. COR	CONTROLO	REF	PVP
570	7.8	1482	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.05U6.930.FI 5245BA.05U6.930.FI	314.8 ☐ 264 ☐
570	7.8	1529	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.05U6.940.FI 5245BA.05U6.940.FI	314.8 ☐ 264 ☐
850	11.8	2223	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.08U6.930.FI 5245BA.08U6.930.FI	398.4 ☐ 347.6 ☐
850	11.8	2293	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.08U6.940.FI 5245BA.08U6.940.FI	398.4 ☐ 347.6 ☐
1130	15.7	2964	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.11U6.930.FI 5245BA.11U6.930.FI	451.3 ☐ 400.7 ☐
1130	15.7	3058	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.11U6.940.FI 5245BA.11U6.940.FI	451.3 ☐ 400.7 ☐
1410	19.6	3704	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.14U6.930.FI 5245BA.14U6.930.FI	537.2 ☐ 486.5 ☐
1410	19.6	3822	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.14U6.940.FI 5245BA.14U6.940.FI	537.2 ☐ 486.5 ☐
1690	23.5	4445	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.16U6.930.FI 5245BA.16U6.930.FI	715.6 ☐ 614.1 ☐
1690	23.5	4586	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.16U6.940.FI 5245BA.16U6.940.FI	715.6 ☐ 614.1 ☐
1970	27.4	5186	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.19U6.930.FI 5245BA.19U6.930.FI	766.3 ☐ 664.9 ☐
1970	27.4	5351	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.19U6.940.FI 5245BA.19U6.940.FI	766.3 ☐ 664.9 ☐
2250	31.4	5927	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.22U6.930.FI 5245BA.22U6.930.FI	829.8 ☐ 728.3 ☐
2250	31.4	6115	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.22U6.940.FI 5245BA.22U6.940.FI	829.8 ☐ 728.3 ☐
2530	35.3	6668	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.25U6.930.FI 5245BA.25U6.930.FI	918.7 ☐ 817.1 ☐
2530	35.3	6880	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.25U6.940.FI 5245BA.25U6.940.FI	918.7 ☐ 817.1 ☐
2810	39.2	7409	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.28U6.930.FI 5245BA.28U6.930.FI	1010.2 ☐ 908.7 ☐
2810	39.2	7644	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.28U6.940.FI 5245BA.28U6.940.FI	1010.2 ☐ 908.7 ☐
3090	43.1	8150	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.30U6.930.FI 5245BA.30U6.930.FI	1106.5 ☐ 1005 ☐
3090	43.1	8408	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.30U6.940.FI 5245BA.30U6.940.FI	1106.5 ☐ 1005 ☐
3370	47	8891	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5245BA.33U6.930.FI 5245BA.33U6.930.FI	1181 ☐ 1079.5 ☐
3370	47	9173	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5245BA.33U6.940.FI 5245BA.33U6.940.FI	1181 ☐ 1079.5 ☐

SELECIONE A OPÇÃO PREFERIDA

ACABAMENTO	FI	ÂNGULO	BA
Preto Texturado	TB	60°	60
Prateado Texturado	TS		
Branco Texturado	TW		

ACESSÓRIOS



C. de Alim. Encastrada	Preto Texturado	PVP	Prateado Texturado	PVP	Branco Texturado	PVP
C. de Alim. Encastrada	80303020.TB	12.00	80303020.TS	12.00	80303020.TW	12.00



C. de Alim. Saliente	Preto Texturado	PVP	Prateado Texturado	PVP	Branco Texturado	PVP
C. de Alim. Saliente	80303021.TB	16.40	80303021.TS	16.40	80303021.TW	16.40



Cabo Aliment. Transpar.	ON/OFF	PVP	DALI Push	PVP
Cabo de Aliment. 1.5m	80303001	5.80	80303004	12.90
Cabo de Aliment. 3m	80303002	11.00	80303005	24.40
Cabo de Aliment. 5m	80303003	20.10	80303006	40.00

Kit de suspensão	Prateado	PVP
------------------	----------	-----



Kit Suspensão 1,5 m (1un)

Kit Suspensão 3 m (1un)

Kit Suspensão 5 m (1un)

80303017.SL

80303018.SL

80303019.SL

7.00

16.90

25.60