


ORIS 50MM TRIM. PRISMATIC - ENCASTRÁVEIS
LIST PRODUCT PRICE - CRI→80

LENGTH	POWER	LED LUMENS	FINISHING	COLOR TEMP.	1-10V	PVP	DALI	PVP	ON/OFF	PVP
850	20,3	3330	AL	3000K	1721V.08P8.8CT.FI	166.60	172DA.08P8.8CT.FI	181.20	172NF.08P8.8CT.FI	142.00
850	20,3	3510	AL	4000K	1721V.08P8.8CT.FI	166.60	172DA.08P8.8CT.FI	181.20	172NF.08P8.8CT.FI	142.00
1130	27	4440	AL	3000K	1721V.11P8.8CT.FI	185.20	172DA.11P8.8CT.FI	199.60	172NF.11P8.8CT.FI	160.40
1130	27	4680	AL	4000K	1721V.11P8.8CT.FI	185.20	172DA.11P8.8CT.FI	199.60	172NF.11P8.8CT.FI	160.40
1410	33,8	5550	AL	3000K	1721V.14P8.8CT.FI	213.60	172DA.14P8.8CT.FI	228.00	172NF.14P8.8CT.FI	188.80
1410	33,8	5850	AL	4000K	1721V.14P8.8CT.FI	213.60	172DA.14P8.8CT.FI	228.00	172NF.14P8.8CT.FI	188.80
1690	40,5	6660	AL	3000K	1721V.16P8.8CT.FI	248.60	172DA.16P8.8CT.FI	263.00	172NF.16P8.8CT.FI	223.80
1690	40,5	7020	AL	4000K	1721V.16P8.8CT.FI	248.60	172DA.16P8.8CT.FI	263.00	172NF.16P8.8CT.FI	223.80
1970	47,3	7770	AL	3000K	1721V.19P8.8CT.FI	330.20	172DA.19P8.8CT.FI	359.20	172NF.19P8.8CT.FI	280.80
1970	47,3	8190	AL	4000K	1721V.19P8.8CT.FI	330.20	172DA.19P8.8CT.FI	359.20	172NF.19P8.8CT.FI	280.80
2250	54	8880	AL	3000K	1721V.22P8.8CT.FI	364.00	172DA.22P8.8CT.FI	393.00	172NF.22P8.8CT.FI	314.60
2250	54	9360	AL	4000K	1721V.22P8.8CT.FI	364.00	172DA.22P8.8CT.FI	393.00	172NF.22P8.8CT.FI	314.60
2530	60,8	10530	AL	4000K	1721V.25P8.8CT.FI	392.60	172DA.25P8.8CT.FI	421.40	172NF.25P8.8CT.FI	343.00
2530	60,8	9990	AL	3000K	1721V.25P8.8CT.FI	392.60	172DA.25P8.8CT.FI	421.40	172NF.25P8.8CT.FI	343.00
2810	67,6	11100	AL	3000K	1721V.28P8.8CT.FI	424.20	172DA.28P8.8CT.FI	453.20	172NF.28P8.8CT.FI	374.80
2810	67,6	11700	AL	4000K	1721V.28P8.8CT.FI	424.20	172DA.28P8.8CT.FI	453.20	172NF.28P8.8CT.FI	374.80
3090	74,3	12210	AL	3000K	1721V.30P8.8CT.FI	465.00	172DA.30P8.8CT.FI	494.00	172NF.30P8.8CT.FI	415.40
3090	74,3	12870	AL	4000K	1721V.30P8.8CT.FI	465.00	172DA.30P8.8CT.FI	494.00	172NF.30P8.8CT.FI	415.40
3370	81	13320	AL	3000K	1721V.33P8.8CT.FI	502.00	172DA.33P8.8CT.FI	531.00	172NF.33P8.8CT.FI	452.60
3370	81	14040	AL	4000K	1721V.33P8.8CT.FI	502.00	172DA.33P8.8CT.FI	531.00	172NF.33P8.8CT.FI	452.60
3930	94,6	15540	AL	3000K	1721V.39P8.8CT.FI	634.40	172DA.39P8.8CT.FI	677.80	172NF.39P8.8CT.FI	560.00
3930	94,6	16380	AL	4000K	1721V.39P8.8CT.FI	634.40	172DA.39P8.8CT.FI	677.80	172NF.39P8.8CT.FI	560.00
4490	108,1	17760	AL	3000K	1721V.44P8.8CT.FI	714.00	172DA.44P8.8CT.FI	757.40	172NF.44P8.8CT.FI	639.80
4490	108,1	18720	AL	4000K	1721V.44P8.8CT.FI	714.00	172DA.44P8.8CT.FI	757.40	172NF.44P8.8CT.FI	639.80
5050	121,5	19980	AL	3000K	1721V.50P8.8CT.FI	794.00	172DA.50P8.8CT.FI	837.40	172NF.50P8.8CT.FI	719.80
5050	121,5	21060	AL	4000K	1721V.50P8.8CT.FI	794.00	172DA.50P8.8CT.FI	837.40	172NF.50P8.8CT.FI	719.80

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI	BEAM ANGLE	BA
1-10V	1V	3000K	30	Anodized aluminium	AL	80°	80
DALI	DA	4000K	40				
ON/OFF	NF						


ORIS 50MM TRIM. PRISMATIC - ENCASTRÁVEIS
LIST PRODUCT PRICE - CRI→90

LENGTH	POWER	LED LUMENS	FINISHING	COLOR TEMP.	1-10V	PVP	DALI	PVP	ON/OFF	PVP
850	19,8	3120	AL	3000K	1761V.08P8.9CT.FI	178.60	176DA.08P8.9CT.FI	193.00	176NF.08P8.9CT.FI	153.80
850	19,8	3260	AL	4000K	1761V.08P8.9CT.FI	178.60	176DA.08P8.9CT.FI	193.00	176NF.08P8.9CT.FI	153.80
1130	26,4	4160	AL	3000K	1761V.11P8.9CT.FI	197.20	176DA.11P8.9CT.FI	211.60	176NF.11P8.9CT.FI	172.40
1130	26,4	4340	AL	4000K	1761V.11P8.9CT.FI	197.20	176DA.11P8.9CT.FI	211.60	176NF.11P8.9CT.FI	172.40
1410	33	5200	AL	3000K	1761V.14P8.9CT.FI	229.60	176DA.14P8.9CT.FI	244.00	176NF.14P8.9CT.FI	204.80
1410	33	5430	AL	4000K	1761V.14P8.9CT.FI	229.60	176DA.14P8.9CT.FI	244.00	176NF.14P8.9CT.FI	204.80
1690	39,6	6240	AL	3000K	1761V.16P8.9CT.FI	266.40	176DA.16P8.9CT.FI	281.00	176NF.16P8.9CT.FI	241.60
1690	39,6	6510	AL	4000K	1761V.16P8.9CT.FI	266.40	176DA.16P8.9CT.FI	281.00	176NF.16P8.9CT.FI	241.60
1970	46,2	7280	AL	3000K	1761V.19P8.9CT.FI	352.20	176DA.19P8.9CT.FI	381.20	176NF.19P8.9CT.FI	302.60
1970	46,2	7600	AL	4000K	1761V.19P8.9CT.FI	352.20	176DA.19P8.9CT.FI	381.20	176NF.19P8.9CT.FI	302.60
2250	52,8	8320	AL	3000K	1761V.22P8.9CT.FI	388.00	176DA.22P8.9CT.FI	417.00	176NF.22P8.9CT.FI	338.40
2250	52,8	8680	AL	4000K	1761V.22P8.9CT.FI	388.00	176DA.22P8.9CT.FI	417.00	176NF.22P8.9CT.FI	338.40
2530	59,4	9360	AL	3000K	1761V.25P8.9CT.FI	420.60	176DA.25P8.9CT.FI	449.40	176NF.25P8.9CT.FI	371.00
2530	59,4	9770	AL	4000K	1761V.25P8.9CT.FI	420.60	176DA.25P8.9CT.FI	449.40	176NF.25P8.9CT.FI	371.00
2810	66	10400	AL	3000K	1761V.28P8.9CT.FI	454.20	176DA.28P8.9CT.FI	483.20	176NF.28P8.9CT.FI	404.80
2810	66	10860	AL	4000K	1761V.28P8.9CT.FI	454.20	176DA.28P8.9CT.FI	483.20	176NF.28P8.9CT.FI	404.80
3090	72,6	11440	AL	3000K	1761V.30P8.9CT.FI	499.00	176DA.30P8.9CT.FI	528.00	176NF.30P8.9CT.FI	449.60
3090	72,6	11940	AL	4000K	1761V.30P8.9CT.FI	499.00	176DA.30P8.9CT.FI	528.00	176NF.30P8.9CT.FI	449.60
3370	79,2	12480	AL	3000K	1761V.33P8.9CT.FI	538.00	176DA.33P8.9CT.FI	566.80	176NF.33P8.9CT.FI	488.40
3370	79,2	13020	AL	4000K	1761V.33P8.9CT.FI	538.00	176DA.33P8.9CT.FI	566.80	176NF.33P8.9CT.FI	488.40
3930	92,4	14560	AL	3000K	1761V.39P8.9CT.FI	676.40	176DA.39P8.9CT.FI	719.80	176NF.39P8.9CT.FI	602.00
3930	92,4	15200	AL	4000K	1761V.39P8.9CT.FI	676.40	176DA.39P8.9CT.FI	719.80	176NF.39P8.9CT.FI	602.00
4490	105,6	16640	AL	3000K	1761V.44P8.9CT.FI	762.00	176DA.44P8.9CT.FI	805.40	176NF.44P8.9CT.FI	687.80
4490	105,6	17370	AL	4000K	1761V.44P8.9CT.FI	762.00	176DA.44P8.9CT.FI	805.40	176NF.44P8.9CT.FI	687.80
5050	118,8	18720	AL	3000K	1761V.50P8.9CT.FI	848.00	176DA.50P8.9CT.FI	891.40	176NF.50P8.9CT.FI	773.80
5050	118,8	19530	AL	4000K	1761V.50P8.9CT.FI	848.00	176DA.50P8.9CT.FI	891.40	176NF.50P8.9CT.FI	773.80

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	COLOR TEMP.	CT	FINISHING	FI	BEAM ANGLE	BA
1-10V	1V	3000K	30	Anodized aluminium	AL	80°	80
DALI	DA	4000K	40				
ON/OFF	NF						


ORIS 50MM TRIM. PRISMATIC - ENCASTRÁVEIS
LIST PRODUCT PRICE - Tunable White CRI→80

LENGTH	POWER	LED LUMENS	FINISHING	COLOR TEMP.	Tunable White	PVP
850	19,8	3525	AL			238.80
1130	26,4	4700	AL			259.80
1410	33	5875	AL			297.40
1690	39,6	7050	AL			334.60
1970	46,2	8225	AL			477.00
2250	52,8	9400	AL			513.40
2530	59,4	10575	AL			550.80
2810	66	11750	AL			585.20
3090	72,6	12925	AL			634.80
3370	79,2	14100	AL			750.80
3930	92,4	16450	AL			869.80
4490	105,6	18800	AL			961.20
5050	118,8	21150	AL			1052.60

SELECT YOUR PREFERRED OPTION

CONTROL TYPE	XX	FINISHING	FI	BEAM ANGLE	BA
Tunable White	TW	Anodized aluminium	AL	80°	80

ACCESSORIES


Trimless Plaster KIT	4 - 5cm	PVP	0.7 - 2.1cm	PVP
Trimless Plaster KIT	80303058	25.00	80303059	25.00