



ORIS S.P.COMBI PR+L3 - TETO
LIST PRODUCT PRICE - CRI→90

LENGTH	POWER	LED LUMENS	FINISHING	COLOR TEMP.	CONTROLO	REF	PVP
1420	22.9	3460	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	484BA.14P8.930.FI 484BA.14P8.930.FI	484.7 ☐ 394.7 ☐
1420	22.9	3460	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	484BA.14P8.940.FI 484BA.14P8.940.FI	484.7 ☐ 394.7 ☐
1700	28	4248	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	484BA.17P8.930.FI 484BA.17P8.930.FI	516 ☐ 426.2 ☐
1700	28	4248	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	484BA.17P8.940.FI 484BA.17P8.940.FI	516 ☐ 426.2 ☐
1980	33.1	5036	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	484BA.19P8.930.FI 484BA.19P8.930.FI	559.5 ☐ 469.5 ☐
1980	33.1	5036	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	484BA.19P8.940.FI 484BA.19P8.940.FI	559.5 ☐ 469.5 ☐
2260	38.2	5824	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	484BA.22P8.930.FI 484BA.22P8.930.FI	662.7 ☐ 528.8 ☐
2260	38.2	5824	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	484BA.22P8.940.FI 484BA.22P8.940.FI	662.7 ☐ 528.8 ☐
2540	43.4	6611	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	484BA.25P8.930.FI 484BA.25P8.930.FI	701.6 ☐ 567.7 ☐
2540	43.4	6611	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	484BA.25P8.940.FI 484BA.25P8.940.FI	701.6 ☐ 567.7 ☐

SELECT YOUR PREFERRED
OPTION

FINISHING	FI	BEAM ANGLE	BA
Textured Black	TB	80°	80
Textured Silver	TS		
Textured White	TW		