

ORIS SLIM PRO LOW GLARE - TETO
LIST PRODUIT PRIX - CRI→90

LONGUEUR	POWER	LED LUMENS	FINITION	TEMP. COULEUR	CONTROLO	REF	PVP
570	7.8	1482	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.05U6.930.FI 5247BA.05U6.930.FI	278.9 ☐ 228.1 ☐
570	7.8	1529	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.05U6.940.FI 5247BA.05U6.940.FI	278.9 ☐ 228.1 ☐
850	11.8	2223	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.08U6.930.FI 5247BA.08U6.930.FI	360.1 ☐ 309.3 ☐
850	11.8	2293	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.08U6.940.FI 5247BA.08U6.940.FI	360.1 ☐ 309.3 ☐
1130	15.7	2964	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.11U6.930.FI 5247BA.11U6.930.FI	403.3 ☐ 352.6 ☐
1130	15.7	3058	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.11U6.940.FI 5247BA.11U6.940.FI	403.3 ☐ 352.6 ☐
1410	19.6	3704	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.14U6.930.FI 5247BA.14U6.930.FI	487.9 ☐ 437.1 ☐
1410	19.6	3822	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.14U6.940.FI 5247BA.14U6.940.FI	487.9 ☐ 437.1 ☐
1690	23.5	4445	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.16U6.930.FI 5247BA.16U6.930.FI	657.3 ☐ 555.9 ☐
1690	23.5	4586	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.16U6.940.FI 5247BA.16U6.940.FI	657.3 ☐ 555.9 ☐
1970	27.4	5186	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.19U6.930.FI 5247BA.19U6.930.FI	708.1 ☐ 606.6 ☐
1970	27.4	5351	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.19U6.940.FI 5247BA.19U6.940.FI	708.1 ☐ 606.6 ☐
2250	31.4	5927	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.22U6.930.FI 5247BA.22U6.930.FI	763.8 ☐ 662.4 ☐
2250	31.4	6115	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.22U6.940.FI 5247BA.22U6.940.FI	763.8 ☐ 662.4 ☐
2530	35.3	6668	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.25U6.930.FI 5247BA.25U6.930.FI	850.2 ☐ 748.7 ☐
2530	35.3	6880	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.25U6.940.FI 5247BA.25U6.940.FI	850.2 ☐ 748.7 ☐
2810	39.2	7409	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.28U6.930.FI 5247BA.28U6.930.FI	936.6 ☐ 835 ☐
2810	39.2	7644	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.28U6.940.FI 5247BA.28U6.940.FI	936.6 ☐ 835 ☐
3090	43.1	8150	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.30U6.930.FI 5247BA.30U6.930.FI	1006.5 ☐ 905.1 ☐
3090	43.1	8408	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.30U6.940.FI 5247BA.30U6.940.FI	1006.5 ☐ 905.1 ☐
3370	47	8891	TB, TS, TW	3000K	DALI / PUSH Dim ON/OFF	5247BA.33U6.930.FI 5247BA.33U6.930.FI	1080 ☐ 978.5 ☐
3370	47	9173	TB, TS, TW	4000K	DALI / PUSH Dim ON/OFF	5247BA.33U6.940.FI 5247BA.33U6.940.FI	1080 ☐ 978.5 ☐

SÉLECTIONNEZ VOTRE OPTION
PRéFéRéE

FINITION	FI	ANGLE	BA
Noir Texturé	TB	60°	60
Argent Texturé	TS		
Blanc Texturé	TW		